



PKR 360 C, low current, ceramic coated, DN 40 CF-F



Similar Image

PKR 360 C, low current, ceramic coated, DN 40 CF-F

- FullRange® gauge with two sensors in one housing
- Optimized for applications in the medium vacuum range
- Very low external magnetic field
- Display range $1 \cdot 10^{-9}$ to 1000 hPa
- Maximum pressure refers to inert gases and temperatures of less than $< 55^\circ\text{C}$
- Rugged and dependable
- Insensitive to air ingress
- Without elastomer seal
- For measuring corrosive media

Technical Data	PKR 360 C, low current, ceramic coated, DN 40 CF-F
Accuracy: 10^{-8} - 10^2 hPa	$\pm 30\%$
Anode	Molybdenum
Bakeout temperature	Elektronics removed, $\leq 150^\circ\text{C}$ Elektronics removed, $\leq 302^\circ\text{F}$ Elektronics removed, $\leq 423\text{ K}$
Feature	Corrosion resistant
Feedthrough	Glass, ceramic coated
Filament	Tungsten
Flange	Stainless steel 1.4435
Measurement range max.	1,000 hPa 750 Torr 1,000 mbar
Measurement range min.	$1 \cdot 10^{-8}$ hPa $7.5 \cdot 10^{-9}$ Torr $1 \cdot 10^{-8}$ mbar
Method of measurement	Pirani/Cold Cathode
Nominal diameter	DN 40 CF-F
Output signal: Minimum load	10 k Ω
Output signal: Pressure range	2.0 - 8.6 V
Output signal: Sensor error above	9.5 V
Output signal: Sensor error below	10.5 V
Pressure max.	10,000 hPa 7,500 Torr 10,000 mbar
Repeatability: 10^{-8} - 10^2 hPa	$\pm 5\%$
Sensor cable length	$\leq 300\text{ m}$ (1 mm ² /Leiter)
Supply: Power consumption max.	2 W
Supply: Voltage	14.5-30 V DC
Temperature: Operating	$5-55^\circ\text{C}$ $41-131^\circ\text{F}$ 278-328 K
Temperature: Storage	$-40-70^\circ\text{C}$ $-40-158^\circ\text{F}$ 233-343 K
Volume	19.9 cm ³
Weight	$< 570\text{ g}$

Order number	
PKR 360 C	PT T02 350 011

Accessories	
Accessory for ActiveLine gauges and controllers	
Mating connector	B 4707 283 MA
Sensor cable, 3 m	PT 448 250 -T

VACUUM SOLUTIONS FROM A SINGLE SOURCE

Pfeiffer Vacuum stands for innovative and custom vacuum solutions worldwide, technological perfection, competent advice and reliable service.

COMPLETE RANGE OF PRODUCTS

From a single component to complex systems:

We are the only supplier of vacuum technology that provides a complete product portfolio.

COMPETENCE IN THEORY AND PRACTICE

Benefit from our know-how and our portfolio of training opportunities!

We support you with your plant layout and provide first-class on-site service worldwide.

Are you looking for a
perfect vacuum solution?
Please contact us:

Pfeiffer Vacuum GmbH
Headquarters · Germany
T +49 6441 802-0
info@pfeiffer-vacuum.de

www.pfeiffer-vacuum.com

All data subject to change without prior notice.