ATS-750-M THERMOSTREAM®

DATASHEET AND SPECIFICATIONS



-90° to +300°C

Advanced Temperature Source for fast and precise thermal conditioning of components, parts, hybrids, modules, subassemblies, and printed circuit boards. Capable of ultra-low temperatures **without** the use of Liquid Nitrogen (LN_2) or Liquid Carbon Dioxide (LCO_2).

PERFORMANCE:

Temperature Range*
-85 to +300°C (50Hz)
-90 to +300°C (60Hz)
No LN_2 or LCO_2 Required

Transition Rate*
-55 to +125°C, approx. 10 seconds or less
125 to -55°C, approx. 10 seconds or less

System Airflow Output*
4 to 18scfm (1.9 to 8.5 l/s) Continuous

* under nominal operating conditions
ultimate low (±1.0°C) achieved at 18scfm
ultimate high (±1.0°C) achieved at 16scfm


TEMPERATURE CONTROL:

Temperature Display & Resolution
+/- 0.1°C

Temperature Accuracy
1.0°C (when calibrated against NIST standard)

DUT Temperature Control
proprietary control algorithm enables DUT temperature to be directly controlled

DUT Sensor Ports
internal diode, thermocouples (T & K), RTD (100 Ohm platinum)




OPERATOR SCREEN

FEATURES:

- **Frost Free Feature**
  dry air purge for tester interface, prevents condensation: 0.5 to 3scfm (0.25 to 1.5 l/s)
- **ECO Friendly Features**
  Automatic Power Reduction
  reduces power usage during idle periods
  Heat Only Mode
  reduces power usage when cold temperatures are not used
- **Heated Defrost Feature**
  quickly removes moisture buildup from internal chiller
- **Fully Adjustable Thermal Head**
- **Thermal Cap**
  5.5 inch ID, High Temperature Rated Thermal Cap or optional

- Windows® OS
- Local & Remote Operations
- LabView™ & LabWindows® drivers
- On-Screen Help
- Ethernet, IEEE-488, RS232 ports
- USB, keyboard, mouse, & printer ports
- customizable and savable test setups
- Program & Datalog Storage (via ethernet or USB)
- User Defined Temperature Limits




DATALOG SCREEN

inTEST Thermal Solutions
TEMPTRONIC CORPORATION


Specifications

ATS-750-M THERMOSTREAM®
Advanced Temperature Source

System Dimensions - Standard



System Dimensions - Extended Height



Weights and Dimensions

Base [1]	Width: 61.0 cm (24 in.), Depth: 72.4 cm (28.5 in.) Height: 108 cm (42.5 in.)
System Weight	Not packed: 236 kg (520 lbs.) Packed: 365 kg (805 lbs.)
Mobility	Four static dissipative, swivel caster wheels
Maximum Reach	160.0cm (63 in.)
Maximum Operating Height	130.3 cm (51.2 in.) - extended height option: 188.0 (74.0 in.)
Minimum Operating Height	69.1 cm (27.2 in.) - extended height option: 81.3 (32.0 in.)
Noise Level	<65dBA

[1] an additional 20.3cm (8 in.) clearance is required for supply connections and cabinet ventilation

Service and Safety

Refrigerants	HCFC and CFC-free, non-toxic, non-flammable
Serviceability	Auto-diagnostics and field replaceable modules
Over Temperature Protection	+305°C (factory set): Operator can set high and low air temperature limits

Facility Requirements

Power [2]	200 - 250 VAC (230V nominal), 50/60Hz 30 amp, 1 phase
Compressed Air [3]	
Clean, Dry Air (CDA)	Filtered to 5 micron particulate contamination. Oil Content: <0.1 ppm, by weight, filtered to 0.01 micron oil contaminant. Dewpoint: <10°C @ 6.2 BAR (90PSI)
Air Supply Pressure	6.2 to 7.6 BAR (90 to 110 PSIG)
Total Air Flow Rate Required	7.1 to 14.2 l/s (15-30 scfm) 11.8 l/s (25 scfm) nominal
Air Supply Temperature	+20° to +25°C; +22°C nominal
Operating Environment [3]	
Operating Temperature	+20° to +28°C; +23°C nominal
Humidity	0 to 60%; 45% nominal

[2] System is configured for operation within voltages listed above using an internal transformer. Please specify power configuration with order

[3] Under operating conditions which are greater or less than nominal, performance may be less than specification provided

inTEST Thermal Solutions
TEMPTRONIC CORPORATION

inTEST Thermal Solutions
41 Hampden Road
Mansfield, MA 02048
TEL: 1.781.688.2300
www.inTESTthermal.com
www.hakuto-vacuum.com.tw

ISO 9001 Certified

CE