PFEIFFER VACUUM

Hakuto 伯東



HiPace® 700


Maximum vacuum performance in a compact design with a pumping speed of 685 l/s for N_2

HiPace® 700 Plus with TC 400, DN 160 ISO-F




Similar Image

- Compact yet powerful turbopump with a pumping speed of 685 l/s for N_2
- Integrated TC 400 drive electronics
- Low vibration and magnetic field - ideal for analytical systems with high requirements
- Extensive accessories expand the range of applications



Dimensions



Technical Data	HiPace® 700 Plus with TC 400, DN 160 ISO-F
Bearing	Hybrid
Compression ratio for Ar	> $1 \cdot 10^{11}$
Compression ratio for H_2	$4 \cdot 10^5$
Compression ratio for He	$3 \cdot 10^7$
Compression ratio for N_2	> $1 \cdot 10^{11}$
Cooling method, optional	Air
Cooling method, standard	Water
Cooling water consumption	100 l/h
Cooling water temperature	15-35 °C | 59-95 °F | 288-308 K
Electronic drive unit	with TC 400
Flange (in)	DN 160 ISO-F
Flange (out)	DN 25 ISO-KF / G 1/4"
Fore-vacuum max. for N_2	11 hPa | 8.25 Torr | 11 mbar
Gas throughput at full rotational speed for Ar	3.5 hPa l/s | 2.62 Torr l/s | 3.5 mbar l/s
Gas throughput at full rotational speed for H_2	> 14 hPa l/s | > 10.5 Torr l/s | > 14 mbar l/s
Gas throughput at full rotational speed for He	20 hPa l/s | 15 Torr l/s | 20 mbar l/s
Gas throughput at full rotational speed for N_2	6.5 hPa l/s | 4.88 Torr l/s | 6.5 mbar l/s
Interfaces	RS-485, Remote

Technical Data	HiPace® 700 Plus with TC 400, DN 160 ISO-F
Low vibrations	yes
Mounting orientation	vertical, flange up
Operating voltage	24 (± 5 %) V DC
Permissible magnetic field max.	6 mT
Protection category	IP 54
Pumping speed for Ar	665 l/s
Pumping speed for H_2	555 l/s
Pumping speed for He	655 l/s
Pumping speed for N_2	685 l/s
Rotation speed ± 2 %	49200 min^{-1}
Rotation speed variable	60-100 %
Run-up time	4 min
Sound pressure level	50 dB (A)
Ultimate pressure according to PNEUROP	< 1 · 10^{-7} hPa | < 7.5 · 10^{-8} Torr | < 1 · 10^{-7} mbar
Venting connection	G 1/8"
Weight	12.1 kg | 26.68 lb

Order number	
HiPace® 700	**PM P04 442**

Accessories	
Accessory for TC 400/1200 and TM 700	
Y-connector, shielded, M12 for accessories	**P 4723 013**
Adapter and control cables	
Control cable for pumping stations 0.7 m	**PM 061 675 AT**
HiPace - ACP connection cable	**PM 071 142 -X**
Air cooling	
Air cooling for HiPace 400/700 and 800 with TC 400	**PM Z01 303**
Connection cables	
Connection cable for HiPace with TC 400/TM 700 to power supply TPS/DCU 310/311/400/401	**PM 061 352 -T**
Control and display units	
Accessories package for HPU 001/PC	**PM 061 005 -T**
DCU 002, Display Control Unit	**PM 061 348 -T**
HPU 001, Handheld Programming Unit	**PM 051 510 -T**
DCU with integrated power supply	
DCU 310, Display control unit incl. power supply	**PM C01 822**
DN ISO-F, Mounting kit	
Mounting kit for DN 160 ISO-F, including coated centering ring, hexagon screws	**PM 016 460 -T**
Mounting kit for DN 160 ISO-F, including coated centering ring, protection screen, hexagon screws	**PM 016 462 -T**
Mounting kit for DN 160 ISO-F, including coated centering ring, protection screen, stud screws	**PM 016 467 -T**
Mounting kit for DN 160 ISO-F, including coated centering ring, splinter shield, hexagon screws	**PM 016 461 -T**
Mounting kit for DN 160 ISO-F, including coated centering ring, splinter shield, stud screws	**PM 016 466 -T**
Mounting kit for DN 160 ISO-F, including coated centering ring, stud screws	**PM 016 465 -T**
DN ISO-K / -F, sealings, splinter shields, protection screens	
Centering ring with multifunction coating, DN 160 ISO-K/-F	**PM 016 216 -U**
Centering ring with multifunction coating and integrated protection screen, DN 160 ISO-K/-F	**PM 016 218 -U**
Centering ring with multifunction coating and integrated splinter shield, DN 160 ISO-K/-F	**PM 016 217 -U**
Fore-vacuum safety valves	
TVV 001 fore-vacuum safety valve, 115 V AC	**PM Z01 206**
TVV 001 fore-vacuum safety valve, 230 V AC	**PM Z01 205**
Interface and extension cables	
Interface cable, M12 m straight / M12 m straight, 3 m	**PM 061 283 -T**
Mains cables	
Mains cable 115 V AC, NEMA 5-15 to C13, 3 m	**P 4564 309 ZE**
Mains cable 208 V AC, NEMA 6-15 to C13, 3 m	**P 4564 309 ZF**
Mains cable 230 V AC, CEE 7/7 to C13, 3 m	**P 4564 309 ZA**
Relay boxes	
Backing pump relay box, single phase 20 A, for TC 400 and TCP 350, M12 plug	**PM 061 375 -T**
Relay box, shielded, for backing pumps, 1-phase 7 A for TC 400/1200, TM 700 and TCP 350, M12	**PM 071 284 -X**
RS-485	
Power separator for RS-485	**PT 348 132 -T**
Termination resistor for RS-485	**PT 348 105 -T**
USB converter to RS-485 interface	**PM 061 207 -T**
Y-Connector M12 to RS-485	**P 4723 010**

Accessories	
Sealing gas	
Sealing gas throttle for HiPace 300 - 800	**PM Z01 317**
Sealing gas valve, shielded for HiPace 300/400/700 and 800 with TC 400 and TM 700	**PM Z01 312**
TPS-19" rack module	
Front panel kit for TPS 311	**PM 061 395 -T**
TPS 311, mains pack 19" rack module 3HU	**PM 061 346 -T**
TPS wall rail fitting	
TPS 310, mains pack for wall/standard rail fitting	**PM 061 342 -T**
Wall rail fitting for TPS 110/180/310/400	**PM 061 392 -T**
Venting accessory with small flange, G 1/8", hoses, air drier	
TTV 001, dryer for venting turbopumps	**PM Z00 121**
Venting valve (normally closed)	
Venting valve, shielded, 24 V DC, G 1/8", for connection to TC 400/1200 and TM 700	**PM Z01 291**
Vibration damper	
Vibration damper for HiPace with DN 160 ISO-K/F	**PM 006 492 -X**